

# TOGGLE SWITCH

HEAVY DUTY 2HP 20/15A 125/277V AC

T-Switch®

- ♦ Lead Wires up to 12" in Length!
- ♦ Sturdy Construction Body
- ♦ Silicone Boot and Gasket Included
- ♦ 1/2" Panel Opening
- ♦ Preassembled with On/Off Face Plate
- ♦ UL Recognized Special Use Component

*class 2 U.S. and Canada certified*



E355116 SWITCH  
E313209 BOOT



**MAXBrite**  
LED LIGHTING TECHNOLOGY

# T-Switch®

## INSTALLATION INSTRUCTIONS

- 1) Drill 1/2" hole through mounting surface. De-burr.
- 2) Remove one nut, on/off plate and gasket, leaving one nut and lock-washer on switch.
- 3) With switch in mounting hole, check that barrel extends 3 to 4 threads beyond face mounting surface.
- 4) Adjust nut on switch to achieve proper mounting distance.
- 5) Place switch in mounting hole. For dry locations, slide "on/off" plate over barrel, followed by nut , and tighten.
- 6) For wet damp locations, slide gasket, followed "on/off" plate, **DO NOT USE 2nd NUT SUPPLIED.**  
Slip water protection boot/nut over toggle and tighten against on/off plate surface to create water seal.

